





hydraut

All hydraulic products are developed, customized and tested in Italy. Warranty of 24 months.



HA6VM Axial piston motors variable displacement

FEATURES

- AVAILABLE DISPLACEMENT: 55-80-107-160-200 cm³/rev
- WORKING PRESSURE: 400 bar
- PEAK PRESSURE: 450 bar
- AVAILABLE CONTROLS: Proportional hydraulic control HD*, Proportional electrical control EP*, Two-point electrical control EZ*, Two point hydraulic control HZ*, Automatic control HA*
- Interchangeable with Rexroth A6VM

MAIN APPLICATIONS

- Mobile and construction equipment
- Harvesters
- Cranes

HA2FO Axial piston pumps fixed displacement

FEATURES

- AVAILABLE DISPLACEMENT: from 10 to 180 cm³/rev
- WORKING PRESSURE: 400 bar
- PEAK PRESSURE: 450 bar
- Interchangeable with Rexroth A2FO

MAIN APPLICATIONS

- Mobile and construction equipment
- Concrete mixers
- Cranes
- Sweepers





HA4VG Axial piston pumps closed loop

FEATURES

- AVAILABLE DISPLACEMENT: 56-63-71-90-100 cm³/rev
- WORKING PRESSURE: 400 bar
- PEAK PRESSURE: 450 bar
- AVAILABLE CONTROLS: HW hydraulic proportional control, EP1/EP2 electrical proportional control
- Interchangeable with Rexroth A4VG

MAIN APPLICATIONS

- Mobile and construction equipment
- Agriculture machines
- Harvesters
- Cranes



HA2FM Axial piston motors fixed displacement

FEATURES

- AVAILABLE DISPLACEMENT: from 23 to 180 cm³/rev
- WORKING PRESSURE: 400 bar
- PEAK PRESSURE: 450 bar
- Interchangeable with Rexroth A2FM

MAIN APPLICATIONS

- Mobile and construction equipment
- Concrete mixers
- Sweepers



Online on Fluid-Hub.net

HSP - 10V0 | Variable displacement axial piston pumps

FEATURES

- MAX DISPLACEMENT: form 18 to 140 cm³/rev
- WORKING PRESSURE: 280 bar
- PEAK PRESSURE: 350 bar
- AVAILABLE CONTROLS: Cut-off/Load sensing/Remote pressure control, Torque limiter, Proportional pressure & flow regulator
- Interchangeable with Rexroth A10VSO and A10VO

MAIN APPLICATIONS

- Mobile and construction equipment
- Agriculture machines
- Marine auxiliary power
- Metal forming and stamping
- Power units



Online on Fluid-Hub.net





Wide range ready for delivery and technical support in the selection of the most suitable filter element for use. Warranty of 12 months.



SFEX Elixir low pressure filter

FEATURES

- Designed for in-line connections
- Handle working pressures up to 1,6MPa (16 bar).
- Flow rate up to 100 lt/min

MAIN APPLICATIONS

- Agriculture machines
- Industrial
- Mobile and construction equipment
- Transmission



Wide stock available and fast international shipping. Warranty of 12 months.



ALP | External gear pumps

FEATURES

- AVAILABLE DISPLACEMENT: from 1,4 to 87 cm³/rev
- WORKING PRESSURE: up to 250 bar
- PEAK PRESSURE: up to 290 bar

MAIN APPLICATIONS

- Mobile and construction equipment
- Agriculture machines
- Sweepers



Online on Fluid-Hub.net



GHP External gear pumps

FEATURES

- AVAILABLE DISPLACEMENT: from 1,4 to 87 cm³/rev
- WORKING PRESSURE: up to 270 bar
- PEAK PRESSURE: up to 310 bar

MAIN APPLICATIONS

- Mobile and construction equipment
- Agriculture machines
- Sweepers



Online on Fluid-Hub.net





ALM External gear motors

FEATURES

- AVAILABLE DISPLACEMENT: from 1,4 to 87 cm³/rev
- WORKING PRESSURE: up to 250 bar
- PEAK PRESSURE: up to 270 bar

MAIN APPLICATIONS

- Mobile and construction equipment
- Agriculture machines
- Sweepers



Online on Fluid-Hub.net



Interchangeability with Parker Denison and wide stock available. Warranty of 12 months.



VT6GCC - PTO Direct drive vane pumps

FEATURES

- AVAILABLE DISPLACEMENT: from 10,0 to 100 cm³/rev
- WORKING PRESSURE: 240 bar
- AVAILABLE CONFIGURATION: Single & double pump

MAIN APPLICATIONS

- Garbage trucks
- Mobile and construction equipment
- Agriculture machines



Online on Fluid-Hub.net



VT6DCC | Fixed displacement vane pumps

FEATURES

- AVAILABLE DISPLACEMENT: from 10,0 to 190,5 cm³/rev
- WORKING PRESSURE: 240 bar


MAIN APPLICATIONS

- Garbage trucks
- Mobile and construction equipment
- Agriculture machines



Online on Fluid-Hub.net





VT6CCZ | Fixed displacement vane pumps

FEATURES

- AVAILABLE DISPLACEMENT: from 10,0 to 100 cm³/rev
- WORKING PRESSURE: 240 bar
- SPECIAL FEATURE: Roller bearing on rear cartridge

MAIN APPLICATIONS

- Garbage trucks
- Mobile and construction equipment
- Agriculture machines



Online on Fluid-Hub.net



Web portal of our products

On Fluid-Hub.net you can benefit of a 2% discount for all orders that you will submit on the platform.



